




Active Head OZONE


Syro-stabilized head Active Head OZONE




The design of this head allows to use all of the common types of film and digital cameras. Precision mechanics and newest unique software makes it extremely reliable and easy to use at the same time. The head is equipped with a digital lens control system that adds functionality and flexibility. It's available with a variety of control options such as Handwheels, Joystick and Pan Bar*.







Features:



- High angular velocity on all axes
- Compact Size and Light Weight
- Fast and effective rebalancing and calibration
- Solid and reliable construction
- Axis position indication
- **Quick Assembly**
- Remote controlled handling of lens Parameters (Focus, Iris, Zoom)
- Auto horizon
- Control capability by cable or wireless
- 360 degree pan and roll function

Widht	755 mm/ 29.7 in
Depth	208 mm/ 8.1 in
Power Supply AC	(90-264V); 1000W (peak)
Power Supply DC	(19-72V); 1000W (peak)
Pan angular speed	270 deg/sec
Tilt angular speed	270 deg/sec
Roll angular speed	270 deg/sec
Weight	30 kg/ 66.14 lbs
Maximum usable focal length	290 mm
Payload	45 kg/ 99.2 lbs

This model fits for all of the common types of Cranes, Remote Controlled Platforms and Helicopter/Aerial Systems.



